

Maintenance oil



5L 1L

As with all wood finishing always do a test area first to safeguard against an undesirable outcome. This technical data sheet is merely a guide and not a guarantee. All products are formulated to the best of our knowledge. The information is given as a result of many years experience. This product has had extensive tests carried out.

Produced by Debal Coatings nv

Industrieweg 29 - 8800 Beveren-Roeselare

Belgium

tel. +32 (0) 51 30 11 40

fax +32 (0) 51 31 26 48

ciranova@ciranova.be

PRODUCT DESCRIPTION

Universal maintenance system for oiled wooden floors. For the maintenance of floors treated with flooring oil, waxoil and UV-oil. Different colours available.

TECHNNICAL DATA

FYSISCHE TOESTAND	fluid
APPEARANCE	dark yellow
SOLID CONTENT	26%

USE

To maintain floors treated with flooring oil, wax oil and UV-oil.

PREPARATION

With Flooring Oil or Wax Oil treated wood: remove soap rests with pure water and let dry. If strongly dirty, clean first with Intensive Cleaner Ciranova®.

USER TIPS

Apply a thin layer of Maintenance Oil Ciranova® and let impregnate for a few minutes. Whipe of white a clean cloth.



DRYING TIMES

First 24 hours do not charge! By hand: drying time ±4 hours, mechanical directly dry. Optimum hardness is reached after 4 hours. During this period, do not treat with water.



APPLYING QUANTITY

50 m²/l for the maintenance of already treated wooden floors.

AFTER TREATMENT

It has been advised to treat the floor each year with Maintenance Oil Ciranova®.

SPECIAL QUALITIES

Used cloths need to be thrown into water after use, to increase flamability. The presence of linseed oil in the system causes this measure. Oil Refresh Ciranova® protects your parquet floor against water and your wood gets a natural view.